

LMR25MM-200HT | Battery Cell

ENGINEERED POWER, BATTERY DATA SHEET




DOT Tested · Hermetically Sealed · High Quality · Reliable & Safe

Serviceability is part of our promise. Engineered Power's global network of engineers provides localized expert design, experienced service knowledge, and timely product delivery where you want it and when you need it.

Battery Features

- primary
- lithium thionyl chloride
- high energy
- extreme high temperature
- moderate rate
- custom terminations



Technical Data

Capacity:
9.0 AH Nominal

Voltage:
3.67 V OCV
3.56 V CCV – 200 mA, 200°C

Constant Current Capability:
200 mA Nominal
400 mA Max

Operating Temperature:
+158°F to +392°F
+70°C to +200°C

Physical Data

Diameter:
0.96 inch ± 0.010 (24.4 mm)

Height:
3.85 inch ± 0.050 (97.8 mm)

Weight:
3.4 ounces (96 grams ± 5)

Shock & Vibration Data

UN/DOT Certified

Shock Test:
1,000G 0.5 ms shocks in X, Y, Z axis at 150°C for 10 shocks

Vibration Test:
40GRMS vibration at 150°C

Suitable Applications

Measurement while drilling (MWD), down hole & pressure gauge applications, memory backup, high shock & vibration applications.

Minimize Your Risk and Maximize Your Power!



ENGINEERED POWER

www.engineeredpower.com | email info@engineeredpower.com

#20, 3103 - 14 Avenue N.E.
Calgary, Alberta, Canada
T2A 7N6

1750 Evergreen Street
Duarte, California, USA
91010