

LMRCC-DA-200HT | Battery Cell

ENGINEERED POWER, BATTERY DATA SHEET




DOT Tested · Hermetically Sealed · High Quality · Reliable & Safe

Serviceability is part of our promise. Engineered Power's global network of engineers provides localized expert design, experienced service knowledge, and timely product delivery where you want it and when you need it.

Battery Features

- primary
- lithium thionyl chloride
- high energy
- extreme high temperature
- moderate rate
- custom terminations



Technical Data

Capacity:
9.5 AH Nominal

Voltage:
3.67 V OCV
3.62 V CCV - 200 mA, 200°C

Constant Current Capability:
200 mA Nominal

Operating Temperature:
+158°F to +392°F
+70°C to +200°C

Physical Data

Diameter:
0.99 inch \pm 0.010 (25.1 mm)

Height:
3.81 inch \pm 0.050 (96.8 mm)

Weight:
3.5 ounces (100 grams \pm 5)

Shock & Vibration Data

UN/DOT Certified

Shock Test:
1,000G 0.5 ms shocks in X,Y, Z axis for 10 shocks

Vibration Test:
40GRMS vibration

Suitable Applications

Measurement while drilling (MWD), downhole & pressure gauge applications, memory backup, high shock & vibration application.

Minimize Risk. Maximize Your Power.

Tel 403 235 2584
info@engineeredpower.com



POWERED BY
LITHION

Updated: May 2021